

Fibro agro board



- Agro board panel WW in accordance with DIN EN 13168
- Wood wool panel, mineral-bonded, fine wool (approx. 2 mm)
- T1-L3-W2-P2-CS(10)200-CI2-S2

Properties:

- Safe according to building biology principles
- Difficult to ignite, B-s1, d0, non-smouldering
- Good sound absorption
- High vapour permeability
- Certificate of Constancy of Performance no. 0800-CPR-III-1081-2

Colour:

- Standard version: natural

Alternatively, for an additional charge:

- White, wipeable coating, RAL 9010
- Other colours on request, please indicate the RAL or NCS number

Area of application:

- Permeable ceiling cladding for agricultural buildings, providing optimal ventilation, e.g. for animal housing.
- Application type in accordance with DIN V 4108-10: DI dm/WI dm

Thickness in mm	R ₀ [m ² ·K/W] ¹⁾	R [m ² ·K/W] ²⁾	Weight in kg/m ²	Amount per pallet in m ²	Standard version: 2,400 × 600 mm Special version: 1,200 × 600 mm	Pallet size in mm			Amount in m ² per truck unloaded by forklift
					Amount per pallet in items	Length	Width	Height	
25	0.35	0.35	10.5	50.4	70	1,200	1,200	1,110	2,217.60
				100.8					
35	0.50	0.50	14.5	40.32	56	1,200	1,200	1,110	1,612.80
				80.64					

¹⁾ Nominal value of the thermal conduction resistance = R₀ ²⁾ Rated value of the thermal conduction resistance = R

This technical information reflects the current level of our knowledge and experience. Subject to change without prior notice. Please use the latest version of this product data sheet, because levels of experience and knowledge are constantly evolving. If in doubt, please contact our office. The application examples described cannot take into account the specific circumstances of each individual case, and we therefore accept no liability for them. In all other respects, only our General Terms and Conditions of Sale, Delivery, and Payment (latest version), of which you are aware, shall apply. November 2022



www.blauer-engel.de/uz132



PEFC/04-31-2168

www.pefc.de



The mark of responsible forestry



0800

All products available with indoor air cleaning effect on request

All products available with FSC Mix wood on request